

B 05 engl PS75Y-PS150Y TC-Y-Adapter R00 hp 0270222.do

Polysulfone Sanitary-Y-Adapter (1-1/2" and 3/4")

Description:

Sanitary-Y-Adapter

1-1/2" (Large-) and 3/4" (Mini-) Sanitary / Tri Clover

Application (examples):

- Capsule Filter Connections
- Connection to DSP- or USP-Systems
- Bag-Systems, etc.

1-1/2 " (Large-) Sanitary-Y-Adapter

Product-Code: PS150Y





Material (Adapter): Polysulfone (USP Class VI) Material (Gaskets): Plat. Cur. Sil.; USP Class VI

Pressure: up to 4,99 bar Temperature: -40 to 149°C

Sterilization: Autoclave (up to 10 cycles);

ETO; Gamma Irr.; E-Beam

With LOT Number for full traceability


All Parts ADCF (Animal Derived Comp. Free)

3/4 " (Mini-) Sanitary-Y-Adapter

Product-Code: PS75Y







Wichtig: Es obliegt der Verantwortung des Benutzers, die Eignung und Sicherheit der Kupplungen von Applied Critical Fluids GmbH (ACF) für alle Anwendungen sicherzustellen. Für einen Zeitraum von 6 Monaten ab ursprünglichem Kaufdatum gewährleistet ACF die Einwandfreiheit des Produkts in Bezug auf Material und Verarbeitung. Unsere einzige Verpflichtung besteht darin, einen jeglichen Teil des Produktes, der sich als schadhaft erweist, zu ersetzen oder nach unserem Ermessen den Kaufpreis desselben zurückzuerstatten. Der Benutzer übernimmt alle anderen Risiken, einschließlich Verletzungsgefahr, Verlust oder Schaden, ob direkt oder indirekt, die durch den Gebrauch den Missbrauch oder der Unfähigkeit dieses Produktes zu benutzen entstehen. DIESE GARANTIE ERSETZT ALLE ZUSICHERUNGEN ALLGEMEINER GEBRAUCHSTAUGLICHKEIT, EIGNUNG FÜR EINEN BESTIMMTEN ZWECK, SOWIE ALLE ANDEREN AUSDRÜCKLICHEN ODER IMPLIZIERTEN GARANTIEN. Abweichungen jeglicher Art werden nicht anerkannt.

ACF übernimmt keinerlei Verantwortung oder Haftpflicht für jegliche bereitgestellten Empfehlungen oder für Werte, die in Bezug auf dieses Produkt ermittelt werden. Das Risiko der Gabe und Annahme von Empfehlungen liegt beim Käufer.

Important: It is the sole responsibility of the user to qualify the suitability and security of the coupling from ACF (Applied Critical Fluids GmbH) for all applications. For a period of 6 months from the purchase date ACF gives warranty on the product regarding material and quality of extrusion. Our sole responsibility is the part of a product which shows a defect, to replace or according to our decision refund the purchase price. The user bears all other responsibilities, risks, including danger of injures, loss or damage, either direct or indirect, which may occur by the use, misuse or impossibility to use the product. THIS WARRANTY REPLACES ALL IMPLICATIONS OF GENERAL USE, USABILITY OR SUITABILITY FOR A SPECIFIC USE AS WELL AS ALL OTHER EXPRESSIVELY GIVEN OR IMPLICATED WARRANTIES. No devictions of these rules are reposted.

ACF does not take any responsibility or warranty for any recommendations or for suggestions or results which deriving from this product. The risk to give or to accept of recommendations is with the buyer resp. user of this product.